

# Klixon Pressure Switches

MARS SERIES **333**



## Condenser Fan Cycling Switches

Fan cycling switches provide refrigeration and air conditioning from low ambient conditions.

### Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 1/4" female flare S.A.E. mounting
- 18" leads

### Features:

- Tamper proof construction
- Direct mounting on tubing
- UL & CSA recognized



43301

### Fan Cycling - Close on Pressure Rise

3 SERIES MARS NO.	4 SERIES MARS NO.	CUT OUT	CUT IN	NOTES
33340	43301	75	100	1/4" Female Flare S.A.E. Mounting
	43302	110	170	1/4" Female Flare S.A.E. Mounting
	43303	125	265	1/4" Female Flare S.A.E. Mounting
	43304	150	225	1/4" Female Flare S.A.E. Mounting
	43305	190	275	1/4" Female Flare S.A.E. Mounting
33341	43370	180	240	New! 1/4" Female Flare
	43306	210	275	1/4" Female Flare S.A.E. Mounting
	43307	300	400	1/4" Female Flare S.A.E. Mounting



43312

### Manual Reset - High Pressure Cut Out Open on Pressure Rise

3 SERIES MARS NO.	4 SERIES MARS NO.	CUT OUT	CUT IN	NOTES
33350 33352	43312	375	Manual	1/4" Female Flare S.A.E. Mounting
	43313	410	Manual	1/4" Female Flare S.A.E. Mounting
	43314	415	Manual	Capillary Tube
	43315	440	Manual	Capillary Tube
	43316	475	Manual	1/4" Female Flare S.A.E. Mounting
	43368	590	Manual	1/4" Female Flare w/snubber
	43369	610	Manual	1/4" Female Flare w/snubber