



Pressure Switches

MARS SERIES **339**



Fixed Setting Pressure Controls

Low pressure controls.

Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 18" leads

Features:

- Tamper proof construction
- Direct mounting on tubing
- UL & CSA recognized

Low Pressure Control, Automatic Reset, Normally Open

MARS2 NO.	MODEL NO.	OPENING PRESSURE	RESET PRESSURE	SWITCH ACTION (OPEN ON PRESSURE)	MOUNTING	APPLICATION
33929	PS80-K2-F0305-020-005	5	20	Fall	1/4" Female S.A.E.	Low Pressure Control
33930	PS80-K2-F0307-025-010	10	25			
33933	PS80-K2-F0312-035-015	15	35			
33962	PS80-K2-F0316-050-025	25	50			
33936	PS80-K2-F0323-065-025	25	65			
33963	PS80-K2-F0325-080-025	25	80			
33964	PS80-K2-F0326-080-040	40	80			
33939	PS80-K2-F0328-090-050	50	90			



Condenser Fan Cycling Switches

Manual reset high pressure controls.

- MARS #33965 has 48" blue leads

MARS2 NO.	MODEL NO.	OPENING PRESSURE	RESET PRESSURE	SWITCH ACTION (OPEN ON PRESSURE)	MOUNTING	APPLICATION
33940	20PS116KA264G126G	126	264	Fall	1/4" Female S.A.E.	Condenser Fan Cycling Switch
33941	20PS107KA275K210K	210	275			
33965	29PSL012-32	410	290	Rise	1/4" Female S.A.E.	H.P.C.
33950	29PSL004-13	415	Manual	Rise	Solder Line Remote Panel, with Capillary Tube	