




Functional Devices, Inc.
 310 South Union Street
 P.O. Box 368
 Russiaville, IN 46979

Office 765.883.5538
Sales 800.888.5538
Fax 765.883.7505
Email sales@functionaldevices.com

MT212 SERIES

MOUNTING TRACK 2.75" Wide Mounting Track for Relays



■ SPECIFICATIONS

Flame Rated: 94-5V

Approvals: UL Component Recognized, USA & Canada
 CE Approved

Mounting: MT212 Series track can be screw-mounted to any flat surface to provide mounting for 2.75" wide track-mountable relays, current sensors, or power supplies.

MT212 SERIES SELECTION GUIDE

MODEL #	WIDTH	LENGTH	DISTANCE BETWEEN HOLE CENTERS
MT212-2	2.75"	2.00"	2.00" Center to Center
MT212-4	2.75"	4.00"	2.00" Center to Center
MT212-6	2.75"	6.00"	2.00" Center to Center
MT212-8	2.75"	8.00"	2.00" Center to Center
MT212-12	2.75"	12.00"	2.00" Center to Center
MT212-18	2.75"	18.00"	2.00" Center to Center
MT212-24	2.75"	24.00"	2.00" Center to Center
MT212-48	2.75"	48.00"	2.00" Center to Center

NOTES