$\mu F$  $\mu F$  $\mu F$ μF  $\mu F$  $\mu F$  $\mu F$  $\mu F$  $\mu F$  $\mu F$  $\mu F$ μF  $\mu F$  $\mu \mathbf{F}$  $\mu \mathbf{F}$  $\mu \mathbf{F}$  $\mu F$  $\mu F$  $\mu \mathbf{F}$  $\mu \mathbf{F}$ 

μF.



| DATE PREPARED:  |          | REVISED:   |  |         |             |  |
|---|----------|--|--|---------|-------------|--|
| August 1, 1992<br>SECTION I                           |          |  | 1/25/01  |         |             |  |
| MANUFACTURER'S NAME Barker Microfarads                |          | EMERGENCY TELEPHONE NUMBER 276-728-9121 CHEMICAL NAME AND SYNONYMS |  |         |             |  |
| ADDRESS (Number, Street, City, S<br>P.O. Box 697      | and Zip) |  |  |         |             |  |
| 205 Mill Street<br>Hillsville, VA 24343               |          |  | TRADE AND SYNONYMS<br>A-99                                 |         |             |  |
|   |          |  | CHEMICAL FAMILY Electrolyte FORMULA                        |         |             |  |
| SECTION II—HAZARDOUS ING                              | REDI     | ENTS   |  |         |             |  |
| Paints, Preservatives, & Solvents Pigments            | %        | TLV(units  | Alloys and Metallic Coatings<br>Base Metal                 | %       | TLV (units) |  |
| Catalyst  |          |  | Alloys   |         |             |  |
| Vehicle   |          |  | Metallic Coatings  |         |             |  |
| Solvents  |          |  | Filler Metal Plus Coating<br>or Core Flux                  |         |             |  |
| Additives   |          |  | Others   | -       |             |  |
| Others  |          |  |  |         |             |  |
| Hazardous Mixtures of Other Liquids, Solids, or Gases |          |  |  |         | TLV (units) |  |
| Ethylene Glycol                                       |          |  |  |         | 50ppm       |  |
| Inorganic Salt of Boric Acid                          |          |  | · · · · · · · · · · · · · · · · · · ·                      |         | N/A         |  |
| SECTION III—PHYSICAL DATA                             |          |  |  |         |             |  |
| BOILING POINT (F°)                                    | 268      |  | SPECIFIC GRAVITY g/cm <sup>3</sup> (H <sub>2</sub> 0=1.00) | 1.24    |             |  |
| VAPOR PRESSURE (mm Hg)                                | N/A      | A  | PERCENT VOLATILE BY VOLU                                   | JME (%) | N/A         |  |
| VAPOR DENSITY (Air=1)                                 | N/A E    |  | EVAPORATION RATE   |         | <<1         |  |
| SOLUBILITY IN WATER Completely Soluble                |          |  |  |         |             |  |
| APPEARANCE AND ODOR Clear and colorless liquid with   | mild     | odor.  |  |         |             |  |

NOTICE: THIS STANDARD CONTAINS PROPRIETARY INFORMATION OF BARKER MICROFARADS, AND IS NOT TO BE REPRODUCED BY ANY METHOD FOR EXTERNAL DISTRIBUTION WITHOUT PRIOR APPROVAL OF A COMPANY OFFICER.

| μF               |
|------------------|
| $\mu$ F          |
| μF               |
| ШF               |
| ШF               |
| WF               |
| WF               |
| WF               |
| ШF               |
| μF               |
| WF               |
| μF               |
| $\mu \mathbf{F}$ |
| μF               |
| μF<br>μF         |
| μF               |
| IIF              |

μF μF μF μF μF μF

 $\mu F$ 

# BARKER (MICROFARADS



| SECTION IV—  |                       |             |                        |            |                 |  |              |  |
|--|-----------------------|-------------|------------------------|------------|-----------------|--|--------------|--|
| FLASH POINT (METHOD USED)  |                       |             | FLAMMABLE LIMITS       |            |                 | LEL  | UEL          |  |
| (Closed Cup; ASTM D-56) >212°F   |                       |             |                        |            |                 | N/A  | N/A          |  |
| EXTINGUISHI  |                       | 7000        | 1000 0000              | on 60 90   | 2 22            | 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  |              |  |
|  | , water, water foan   |             | dioxid                 | le, dry cl | nemical, carbon | tetrachloride  | e            |  |
| Particular designation of the property of the  | FIGHTING PROC         |             |                        |            |                 |  |              |  |
| 1 1  | oool fires directly v |             |                        |            |                 | this can caus  | se frothing. |  |
|  | ined breathing app    |             |                        | ctive clo  | thing.          |  |              |  |
| UNUSUAL FIR  | E AND EXPLOSION       | N HAZARD    | S                      |            |                 |  |              |  |
| None   |                       |             |                        |            |                 |  |              |  |
| SECTION V—I  | HEALTH HAZARD         | DATA        |                        |            |                 |  |              |  |
| THRESHOLD  | LIMIT VALUE           |             |                        |            |                 |  |              |  |
| For vapor and  | mist combined, ba     | ased on eth | hylene                 | e glycol:  | 50ppm ceiling   | (ACG1H 19  | 984-85)      |  |
|  | OVEREXPOSURE          |             |                        |            |                 |  |              |  |
| See attached s   | heet                  |             |                        |            |                 |  |              |  |
| EMERGENCY  | FIRST AID PROCE       | DURES       |                        |            |                 |  |              |  |
| See attached s   | heet.                 |             |                        |            |                 |  |              |  |
| SECTION VI   | REACTIVITY DAT        | Δ           |                        |            |                 |  |              |  |
|  |                       | ' <b>`</b>  |                        |            |                 | Electrical Control of the Control of |              |  |
| STABILITY  | ITY UNSTABLE          |             | ☐ CONDITIONS TO AVOID: |            |                 |  |              |  |
|  | STABLE                |             | $\exists$              |            |                 |  |              |  |
|  | STABLE                |             |                        |            |                 |  |              |  |
|  |                       |             |                        |            |                 |  |              |  |
|  |                       |             |                        |            |                 |  |              |  |
|  |                       |             |                        |            |                 |  |              |  |
| INCOMPATIBI  | LITY (MATERIAL        | S TO AVO    | ID)                    |            |                 |  |              |  |
| Normally unre  | active; however, a    | void stron  | ig bas                 | es at hig  | h temperatures  | strong acids   | s, strong    |  |
| oxidizing ager   | nts and materials re  | eactive wit | th hyd                 | lroxyl co  | mpounds.        |  |              |  |
| HAZARDOUS I  | DECOMPOSITION         | PRODUCT     | S                      |            |                 |  |              |  |
| The state of the s | produce carbon car    |             |                        | and/or c   | arbon dioxide.  |  |              |  |
| HAZARDOUS  |                       | MAY OC      |                        | ТП         | CONDITIONS      | TO AVOID:  |              |  |
|  |                       |             |                        |            |                 |  |              |  |
| WILL   |                       |             | T                      |            |                 |  |              |  |
|  |                       | OCCUR       |                        | -          |                 |  |              |  |
|  |                       |             |                        |            |                 |  |              |  |
|  |                       |             |                        |            |                 |  |              |  |
|  |                       |             |                        |            |                 |  |              |  |

NOTICE: THIS STANDARD CONTAINS PROPRIETARY INFORMATION OF BARKER MICROFARADS, AND IS NOT TO BE REPRODUCED BY ANY METHOD FOR EXTERNAL DISTRIBUTION WITHOUT PRIOR APPROVAL OF A COMPANY OFFICER.



### SECTION VII—SPILL OR LEAK PROCEDURES

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wear suitable protective equipment. Small spills should be flushed with large quantities of water. Larger spills should be collected for disposal.

### WASTE DISPOSAL METHOD

MF

μF μF μF μF

WF

WF

ШF

μF

WF

μF

ШF

μF μF

WF

μF μF μF μF μF

 $\mu F$ 

WF

μF

 $\mu F$ 

MF

 $\mu F$ 

MF

 $\mu F$ 

WF

μF μF μF

 $\mu F$ 

MF

MF

μF μF

 $\mu \mathbf{F}$ 

μF μF

 $\mu \mathbf{F}$ 

μ**F** μ**F** 

 $\mu F$ 

Incinerate in a furnace where permitted under appropriate Federal, State, or local regulations. Contaminated absorbant may be deposited in a landfill in accordance with local, State, and Federal regulations.

#### SECTION VIII—SPECIAL PROTECTION INFORMATION

### RESPIRATORY PROTECTION (SPECIFY TYPE)

If TLV is exceeded, wear NIOSH approved breathing air equipment or NIOSH approved face mask with organic vapor cartridge & dust or mist pre-filter.

| 0                 | 1 8                               | 1      |          |  |
|-------------------|-----------------------------------|--------|----------|--|
| VENTILATION       | LOCAL EXHAUST                     |        | SPECIAL  |  |
|                   | Local exhaust is advisable for el | evated |          |  |
|                   | temperature use.                  |        |          |  |
|                   | MECHANICAL (GENERAL)              |        | OTHER    |  |
|                   | General exhaust is useful.        |        |          |  |
| PROTECTIVE CLOVES |                                   | EVE PR | OTECTION |  |

Monogoggles/Face Shield.

# Rubber or polyvinyl chloride coated.

**OTHER PROTECTIVE EQUIPMENT**Eye bath and safety shower should be available nearby.

# SECTION IX—SPECIAL PRECAUTIONS

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid) all hazard precautions given in this data sheet must be observed.

### OTHER PRECAUTIONS

May be irritating to skin & mucous membranes. Keep away from open flame.

## Effects of Overexposure

Ingestion: May cause discomfort or pain, dizziness, malaise, lumbar pain, oliguria, uremia, central nervous system depression, persistent vomiting and diarrhea followed by profound shock and coma. Severe kidney damage follows swallowing large amounts.

Inhalation: May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations may cause nausea, vomiting, headache, and dizziness.

Eye Contact: May cause discomfort in the eye with transient conjunctivitis. Serious corneal injury is not anticipated.

NOTICE: THIS STANDARD CONTAINS PROPRIETARY INFORMATION OF BARKER MICROFARADS, AND IS NOT TO BE REPRODUCED BY ANY METHOD FOR EXTERNAL DISTRIBUTION WITHOUT PRIOR APPROVAL OF A COMPANY OFFICER.

 $\mu \mathbf{F}$ 

μF μF

μF μF μF

μF μF

WF

μF μF

μF μF

 $\mu F$ 

μF μF

μF

 $\mu F$ 

 $\mu \mathbf{F}$ 

WF

 $\mu F$ 

 $\mu F$ 

 $\mu F$ 

WF

 $\mu F$ 

 $\mu F$  $\mu F$  $\mu F$  $\mu F$ μF  $\mu F$ μF  $\mu F$ WF  $\mu F$ WF WF μF  $\mu F$  $\mu F$  $\mu F$  $\mu F$  $\mu F$  $\mu F$ 

 $\mu F$ 

MF.



Emergency First Aid Procedures:

Ingestion: If conscious, give two glasses of water and induce vomiting. Call a physician immediately.

Skin: Remove contaminated clothing and flush skin with water.

Inhalation: Remove to fresh air. Call a physician if discomfort persists.

Eyes: Immediately flush with water, and continue washing the eyes for several minutes.

The information contained in this data sheet is, to the best of our knowledge and belief, accurate as of the date issued. However, since Barker (BMI) cannot anticipate or control the different conditions under which this information or our products may be used, we make no guarantee that the recommendations will be adequate for all individuals or situations. Each user of the product described herein should determine the safety, toxicity, and suitability of the described product for his particular purpose, and Barker (BMI) assumes no responsibility for damages arising out of the use of the described product. Barker (BMI) makes no warranty, either expressed or implied, regarding the accuracy or reliability of the information in this data sheet, nor shall Barker (BMI) be liable for any loss or damage arising out of the use of the information or the described product.